



NEROLAC IMPRESSIONS SHEEN INTERIOR LUXURY EMULSION



PRODUCT DESCRIPTION

Nerolac Impressions Sheen Emulsion gives your walls a radiant sheen and a rich smooth finish along with low odour. Its faster drying formula speeds up the painting process. The wall stays awe-inspiring for years with excellent stain blocking and superior washability.

The whiteness, opacity, washability, stain resistance, flow & levelling, ease of application, anti-fungal performance and anti-bacterial performance are excellent, thereby creating a high-class smooth radiant sheen finish that keeps the wall awe-inspiring for years.

*It depends upon the quality of surface preparation.

PERFORMANCE FEATURES & BENEFITS



SURFACE PREPARATION

1. Rub the surface using a suitable abrasive paper and wipe it off to ensure that the surface is clean, dry and free from dirt, grease, wax or any other defective or poorly adhering material.
2. Treat fungus affected areas with Nerolac Fungicidal Solution and allow it to react for 6-8 Hrs.
3. Apply 1 coat of Nerolac Perma Damp Protect Interior/Nerolac Premium primer/Popular primer Water/Solvent Thinnable at recommended dilution.
4. Apply 2 coats Nerolac Acrylic Wall Putty or Nerolac Cement Putty to level the dents, dry, followed by sanding with emery paper 180 and wipe clean.
5. Apply 1 coat of Nerolac Perma Damp Protect Interior/Nerolac Premium primer/Popular primer Water/Solvent Thinnable at recommended dilution.
6. Sand the surface with Emery paper no.320 & clean the surface with cloth before painting. Finally, apply 2-3 coats of Nerolac Impressions Sheen at 40-50% dilution. Dark shade may require additional coat for hiding.

RECOMMENDED USAGE

Nerolac Impressions Sheen Luxury Emulsion is designed for application on new as well as previously painted interior surfaces such as plaster, brickwork, cement rendering, concrete, hard boards, etc.

RECOMMENDED SYSTEM FOR APPLICATION:

1. Primer*(1 coat), Dry for 4-6 h.
2. Putty##(1st coat), Dry for 6-8 h.
3. Putty##(2nd coat), Dry for 6-8 h.
4. Primer*(1 coat), Dry for 4-6 h.
5. Finish Nerolac Impressions Sheen (2-3 coats), Dry min for 3-4 Hrs. in between coats.

Sand the surface with Emery paper and clean before application of subsequent coat.

*Nerolac Perma Damp Protect Interior/Nerolac Premium/Popular Primer Water/Solvent Thinnable

##Nerolac Wall putty or Nerolac Cement putty.

For Repainting on Smooth Lime/Distemper/Emulsion/Enamel Masonry Surfaces, skip steps 1, 2 & 3 and start with step 4.

PRECAUTIONS

1. Refer MSDS for "Nerolac Impressions Sheen" for safety measures & precautions.
2. Store in well ambient conditions, ventilated locations & away from the source of ignition and fire.
3. Keep away from children.
4. In case of eye/skin contact, wash with plenty of water.
5. Inhalation/Injection will cause danger. In either case, move to fresh air & consult medical practitioners in both the cases.
6. Do not apply when ambient temperature might drop to level below 10°C within 4 Hrs. of application.
7. New plaster should be allowed to cure for minimum 12 weeks.
8. Avoid extra thinning for better results.
9. Can be tinted with Nerolac Hi-Power Universal Stainer before thinning. Do not add more than 5% of Nerolac Hi-Power Universal Stainer. Stir the tinted paint well, after tinting & before application.
10. The container must be tightly closed when not in use. Stir well and strain before use.
11. Use safety equipment's like rubber or polythene gloves, safety goggles/glasses & face mask.

TECHNICAL DATA



*Actual coverage may vary depending on method & condition of application, surface roughness & surface.

POST APPLICATION INSTRUCTIONS

For removing stains, sponge clean with mild soap solution and wipe clean. Please allow 2 weeks of drying time to freshly painted wall for it to be ready for stain removal/cleaning.



SAFETY FEATURES

Non-Flammable



PACK SIZE

1L, 4L, 10L & 20L



SHADE RANGE

As per Nerolac Color Scapes Fandeck and shade card.



SHELF LIFE

2 years from the date of manufacturing, when stored in the original tightly closed containers, away from direct sunlight and excessive heat.

DISCLAIMER

The product information and application details given by the company has been provided in good faith and is meant to serve only as a general guideline during usage. The performance claims made are based on the tests carried out under controlled conditions and our past experience with the type of products. Therefore actual performance will depend on local factors prevailing at that point of time. Users are advised to carry-out sample tests by taking trials to ensure the suitability of products for their requirement prior to full-scale usage of our products.

The Company is not liable for factors beyond its control such as application during adverse climatic conditions, use of improper application tools/techniques and surface preparation, any structural defects or the inferior quality of materials other than paints. The warranty/guarantee clauses shall accordingly be amended.