



NEROLAC WONDERWOOD GLORIA EPOXY PRIMER



PRODUCT DESCRIPTION

Wonderwood Gloria Epoxy Primer is a universal impreganting primer for both interior and exterior application which blocks tanning and other impurities contained in the wood from reacting with the coating. Thus protecting the wood and providing durable coating, which blocks tannin & moisture contained in the wood and provides excellent durability & finish.

PERFORMANCE FEATURES & BENEFITS



Excellent
Durability & Finish



Block Tannin & Moisture
Contained

SURFACE PREPARATION

1.

Before application, the surface should be clean and free from oil, grease, loose particles, dust, etc.

RECOMMENDED APPLICATION

1. Select the seasoned wood.
2. Sand the surface using sand paper No. 180 followed by sand paper No. 320 or 400 along the grains and wipe off loose dust to clean the surface.
3. Mix wonder wood Gloria Epoxy Primer base and hardener in the ratio 1:1 by volume. Give maturation for 5 – 10 minutes and apply by conventional Spray or Brush. Thinner is not required.
4. Allow to dry for 25-30 minutes. lightly sand the surface with sand paper 320 or 400, Use mixture within 3 – 4 Hours.
5. Slightly sand with emery paper no. 180 & apply 1 – 2 coats of Gloria sealer & then top coat as per recommended process.

NOTE

1. Base should be thoroughly stirred with hardener in given mixing ratio. Strain before use.
2. The base and hardener to be consumed within one week of opening the container. Container should be tightly closed after use.
3. Work in well – ventilated area. Avoid eye and skin contact.
4. For optimum performance Gloria Epoxy Primer must be applied at $30 \pm 10^{\circ} \text{C}$ and humidity less than 75%.

THINNER

Not Required

DISPOSABILITY

Do not pour the leftover sealer down a drain. Seal & keep for disposal. Contains no added Lead, Mercury or Chromium compounds.



POST APPLICATION INSTRUCTIONS

For the best performance, ensure dry dust-cleaning at regular intervals. Allow a drying-time of 2 weeks for proper film-formation before doing any sponge cleaning with a mild soap-solution or mineral turpentine.

STAIN-CLEANING INSTRUCTIONS

- The paint film needs at least a week after application, to be set & ready for the stain-removal.
- Wipe gently. Do not use liquid bleach.
- For light stains like mud, pencil, tea, coffee etc., use a sponge soaked with soap-solution.
- For tougher stains like pickle, oil, grease, wax & oil crayons etc., use a sponge soaked with mineral turpentine.
- The early removal of stains gives better results.

	<p>PACK SIZE 1L & 4 L</p>		<p>SHELF LIFE One year from the date of manufacturing under normal storage condition @ 30° C in original closed container & away from sunlight.</p>
	<p>SAFETY FEATURES Flammable</p>		

DISCLAIMER

The product information and application details given by the company has been provided in good faith and is meant to serve only as a general guideline during usage. The performance claims made are based on the tests carried out under controlled conditions and our past experience with the type of products. Therefore actual performance will depend on local factors prevailing at that point of time. Users are advised to carry-out sample tests by taking trials to ensure the suitability of products for their requirement prior to full-scale usage of our products.

The Company is not liable for factors beyond its control such as application during adverse climatic conditions, use of improper application tools/techniques and surface preparation, any structural defects or the inferior quality of materials other than paints. The warranty/guarantee clauses shall accordingly be amended.