

NEROLAC PERMA

CRACK FILLER क्रैक फिलर



Nerolac Perma Crack Filler is a highly flexible, ready to use and water resistant paste ideally suited for effectively filling & sealing of internal & external plaster cracks.

Product Benefits



Fills up to 10mm cracks



Single coat application



Water resistant



Strong adhesion & flexible



UV resistant

Primary Uses

- Nerolac Perma Crack Filler is ideally suited for filling cracks in plasters whether internal or external
- Nerolac Perma Crack Filler is useful in sealing cracks in the ceilings and at the junctions of brickwork, columns or beams
- Nerolac Perma Crack Filler is highly useful in sealing gaps around door and window frames and around bath tub, wash basin etc.

Coverage

25 – 30 RMT/Kg in 5 mm width x 5 mm depth of crack

Application Method



1
Clean the surface to remove any dust, dirt, spillovers of oil, grease or loose particles. Remove the existing POP or the putty to expose the plaster surface



2
Hairline cracks must be widened up to 2-3 mm width minimum and then filled. Widen the cracks to form 'V' groove and prime the surface with suitable primer



3
Fill one coat using Nerolac Perma Crack Filler not exceeding 10 mm, 3 – 4 cm from each side of the crack



4
Press the paste firmly into the crack with spatula or putty knife and level with the surface. Allow it to dry for overnight. Upon full cure apply putty or POP whatever was removed before the application of Nerolac Perma Crack Filler

Technical Information

PROPERTIES	RESULTS
Appearance	Ready to use white paste
Full time curing, Hours	24
% Elongation	100

Shelf Life

Nerolac Perma Crack Filler has a shelf life of 24 months from the date of manufacture when kept in sealed pack and stored under proper conditions

Storage

Keep in cool and dry place, out of the reach of children

EHS Information

Avoid inhalation, eye and skin contact. In case of contact, wash with water and seek medical attention

Precautions and Recommendations

- Do not apply for cracks of more than 10 mm width
- Refer MSDS before usage
- Further paint application can be taken up once it is full dry

Packing

Nerolac Perma Crack Filler is available in 250 gms & 900 gms pack

DISCLAIMER

KANSAI NEROLAC PAINTS Ltd. (KNPL) warrants that all products are free from any defects of manufactured and comply with the specification given in their respective technical data sheet. No warranty can be given as to the results of use because conditions of use, such as site conditions, surface preparations, workmanship, weather, structural issues and other factors are beyond the control of KNPL . Purchaser agrees to seek the advice of qualified professionals to carry out tests and take trials to determine the suitability of products for their intended purpose prior to full scale usage of **KNPL** products and assumes all risks.

The company does not assume any liability for unsatisfactory results, arising from the use of our products. Purchaser's sole liability is limited to replacement of product or refund of the purchase price paid if any product proven defective. No other warranties express or implied, shall apply including any warranty of merchantability or fitness for particular purpose.

KNPL shall not be liable for any consequential damages arising from the use of our products for unsatisfactory results.

The information supplied in this data sheet is based on our experience through extensive research and is given in good faith in order to help prospective users. We reserve the right to update the information provided in our technical data sheet at any time without prior notice within the scope of technical progress or new developments.